

Emerald Edge Automotive TECHNICAL DATA

PHYSICAL FORM

Liquid – Water thin green liquid with mild odor
pH – approx. 9.0 undiluted

TEMPERATURE LIMITS

32 deg F to 220 deg F

WEIGHT

8.33 lbs/liquid US gallon

SAFETY

RATINGS: NFPA - 1/0/0 HMIS - 1/0/0/A
Wet Flammability – Non-flammable, No VOC's
Dry Flame Spread - N/A
Threshold Limit Value - Non-Toxic
Medical - Not considered a health threat, non-irritating to normal skin. Refer to MSDS

LIMITATIONS

For use on water tolerant materials

APPLICABLE TEST REQUIREMENTS

As required by governing authority.

DISPOSAL

Non-toxic to environment, however, always
check local laws concerning discharge before disposing.

AREAS FOR USE

Any water washable surface, including
floors, walls, concrete, machinery, metal parts, equipment,
vehicles, protective gear, tile, porcelain,
terrazzo, vinyl, plastics, wood, rubber, etc.

COVERAGE

100 sq. ft. to 5,000 sq. ft. per gallon depending on application and method used.
Refer to instructions

TOOLS FOR APPLICATION

Mops, pressure washers, garden type pump-up sprayers,
automatic floor scrubbers, chemical inductors/ proportioners

PACKAGING

5 US gallon plastic pail
55 US gallon plastic drum
Bulk – 275 US gallon tote tanks or larger

SHIPPING

No DOT label required – non-hazardous
Class 55